

21.5 Inch Gaming Monitor

Model : RCS-TM215-LED



<https://www.casino-screen.com>
<https://www.szrcloud.com>

◆ Product Specifications

LCD Monitor		
Series	LED Deco Slim(LED Bezel)	
Display Type	16:9 Ratio, 21.5 inch TFT-LCD	
Active Area	476.64 x 268.11 (mm)	
Monitor Dimensions (WxHxD)	558.8 x 373.1 x 54.4 (mm)	
Suggested Resolution	1920 x 1080 @60Hz, 1080P	
Support Colors	16.7M	
Brightness (Typ.)	Pure LCD Panel	400cd/m ²
	With Touch Monitor	330cd/m ²
Response Time (Typ.)	14 ms	
Viewing Angle (Typ.atCR >10))	Horizontal (left/right)	89°/ 89°
	Vertical (up/down)	89°/ 89°
Contrast Ratio (Typ.)	1000 : 1	
Video Input/Interface	VGA/DVI/HDMI	
Frequency (H/V)	37.9~80KHz / 60~75Hz	
PowerSupply	Type: External Display voltage: DC12V±5% Input(line) voltage: AC100-240V,50-60Hz	
Environment	Operating Temp.	0 ~ 50°C
	Operating RH	10%~90%
	Storage Temp.	-20~60°C
	Storage RH	5%~90%
MTBF	≥30,000 Hours	
LED Backlight Life Time (Typ.)	≥30,000 Hours	
Weight (N.W/G.W)	8.5Kgs / 9.5 Kgs	
Dimensions	558.8 x 373.1 x 54.4 (mm)	
Power Consumption	Stand by Power:≤1.5W/Operating Power:≤30W	
Mount Interface	1. 100 x 200mm 2. Mount bracket, horizontal or vertical mount	
OSD Control	Buttons	AUTO,+,POWER,-,MENU
	Function	Brightness,Contrast Ratio,Auto-adjust,Phase,Clock,H/V Location,Languages,Function,Reset
LED	SMD 5050, 60 LEDs/m	
LED IC / Power	WS2812, 14.4W/m, 12V	

21.5 Inch Gaming Monitor

Touch Screen

Touch Type	21.5 inch Projected Capacitive Touchscreen
Touch Input/Interface	USB
Response Time	≤10ms
Hardness	Min. 7H
Light Transmittance	≥85%
Support System	XP, WIN7, WIN8, WIN10, Linux, Android
Active Area	480.00 x 271.80 (mm)
Cover Glass Thickness	3.0±0.2 (mm)
Touch Test	≥50,000,00
Touch Controller	EETI/ILI/ Siliconworks (optional)

NOTE :

- ① The display SPECS. are adjusted according to the selected LCD screen and touch screen
- ② The support system is adjusted according the specific system and version.

◆ Installation dimension drawing

